

AD-A069 159

HARRY DIAMOND LABS ADELPHI MD

F/G 20/13

AN INITIAL MODEL FOR THE FINITE DISPLACEMENT RESPONSE CHARACTER--ETC(U)

FEB 79 T M DRZEWIECKI

UNCLASSIFIED

HDL-TR-1868

NL

| OF |

AD  
A069159



END

DATE  
FILMED

7-79

DDC

HDL-TR-1868  
February 1979

LEVEL

12  
B.S.

AD A069159

An Initial Model for the Finite Displacement  
Response Characteristics of a Fluidyne Pump

Tadeusz M. Drzewiecki



DDC FILE COPY



U.S. Army Electronics Research  
and Development Command  
Harry Diamond Laboratories  
Adelphi, MD 20783

Approved for public release; distribution unlimited.

79 05 29 099

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

| REPORT DOCUMENTATION PAGE   |   | READ INSTRUCTIONS<br>BEFORE COMPLETING FORM |
|---|---|---|
| 1. REPORT NUMBER<br>(14) HDL-TR-1868  | 2. GOVT ACCESSION NO.   | 3. RECIPIENT'S CATALOG NUMBER<br>(9)        |
| 4. TITLE (and Subtitle)<br>(6) An Initial Model for the Finite Displacement Response Characteristics of a Fluidyne Pump   | 5. TYPE OF REPORT & PERIOD COVERED<br>Technical Report                                |   |
| 7. AUTHOR(s)<br>(10) Tadeusz M./Drzewiecki  | 8. CONTRACT OR GRANT NUMBER(s)<br>DA: 1T161101A91A<br>(16)                            |   |
| 9. PERFORMING ORGANIZATION NAME AND ADDRESS<br>Harry Diamond Laboratories<br>2800 Powder Mill Road<br>Adelphi, MD 20783   | 10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS<br>Program Ele: 6.11.01.A |   |
| 11. CONTROLLING OFFICE NAME AND ADDRESS<br>U.S. Army Materiel Development and Readiness Command<br>Alexandria, VA 22333<br>(11)   | 12. REPORT DATE<br>February 1979  |   |
| 14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)<br>(12) 43 p  | 13. NUMBER OF PAGES<br>45   |   |
| 15. SECURITY CLASS. (of this report)<br>Unclassified  |   | 15a. DECLASSIFICATION/DOWNGRADING SCHEDULE  |
| 16. DISTRIBUTION STATEMENT (of this Report)<br><br>Approved for public release; distribution unlimited  |   |   |
| 17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)  |   |   |
| 18. SUPPLEMENTARY NOTES<br>HDL Project: A107C4<br>DRCMS Code: 61110191A.0011  |   |   |
| 19. KEY WORDS (Continue on reverse side if necessary and identify by block number)<br>Pump            Thermodynamics<br>Fluidyne        Fluidics  |   |   |
| 20. ABSTRACT (Continue on reverse side if necessary and identify by block number)<br>This paper is the final report on the independent laboratory in-house research (ILIR) sponsored work by the Harry Diamond Laboratories on the Fluidyne pump. The effort started with a survey of the extant literature on the subject, continued with experimental observations that led to a mathematical model, and has culminated with a comprehensive statement on the physical operation of the pump. → |   |   |

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE

UNCLASSIFIED

1 SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

163 050

elt

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

The literature is particularly sparse on the subject; hence, only the basic references are cited. The report presents a detailed mathematical model of the fluid mechanical and thermodynamic processes occurring during oscillation. A positive-feedback simulation model is postulated that demonstrates, for the first time, physically why there is an onset of oscillations and subsequent sustained motion. This model is based on actual observations of the startup process in a prototype pump.

The initially reported thermodynamic efficiency of this heat engine was less than 0.3 percent. Currently, Fluidyne pumps have demonstrated efficiencies of about 2 percent. The peak efficiencies, however, may theoretically approach 10 percent. The mathematical model has shown that large losses occur in the heat transfer to the working gas, heat losses to the displacer liquid, and friction in the output line. Improvements in these areas may dramatically improve the observed overall efficiency. The efficiency of the cycle itself, that is, the work done by the thermodynamic cycle relative to the output work, is on the order of 10 percent. Finally, the cycle is shown to be close to a Carnot cycle as opposed to the originally supposed Stirling cycle. This last observation has considerable and significant ramifications as far as future analysis is concerned.

|                                 |   |
|---------------------------------|---|
| ACCESSION for                   |   |
| NTIS                            | White Section <input checked="" type="checkbox"/> |
| DDC                             | Buff Section <input type="checkbox"/>             |
| UNANNOUNCED                     | <input type="checkbox"/>                          |
| CLASSIFICATION                  |   |
| BY                              |   |
| DISTRIBUTION/AVAILABILITY CODES |   |
| no. of SPECIAL                  |   |
| A                               |   |

UNCLASSIFIED



## CONTENTS

|   | <u>Page</u> |
|---|-------------|
| 1. INTRODUCTION .....                             | 5           |
| 2. PHYSICAL DESCRIPTION OF FLUIDYNE STARTUP ..... | 5           |
| 3. MATHEMATICAL MODEL .....                       | 7           |
| 4. NUMERICAL RESULTS .....                        | 14          |
| 5. DISCUSSION AND CONCLUSIONS .....               | 19          |
| LITERATURE CITED .....                            | 22          |
| NOMENCLATURE .....                                | 23          |
| DISTRIBUTION .....                                | 43          |

## APPENDICES

|  |    |
|--|----|
| A.--Temperature Distribution in an Enclosed Cylindrical Gas Volume ..... | 25 |
| B.--Computer Program and Numerical Results .....                         | 37 |

## FIGURES

|   |    |
|---|----|
| 1 Schematic of Fluidyne pump. ....  | 6  |
| 2 Schematic representation of Fluidyne startup process .....                            | 6  |
| 3 Schematic of Fluidyne II used by Geisow .....   | 8  |
| 4 Schematic of actual Fluidyne pump. ....   | 9  |
| 5 Time history of Fluidyne response .....   | 14 |
| 6 Output displacements for various parameters .....                                     | 15 |
| 7 Pressure-volume diagram for first cycle of Fluidyne .....                             | 17 |
| 8 Fluidyne efficiency as function of input temperature and output length .....          | 18 |
| Table I. Comparison of Numerically Computed Fluidyne Frequency with Equation (23) ..... | 16 |

## 1. INTRODUCTION

The introduction of the Fluidyne "no-moving-parts" pump in 1971<sup>1,2</sup> stimulated some new interest in the conversion of low grade, low temperature heat energy into useful work. The basic principle was reported to be a closed Stirling cycle, wherein two adjacent U-tubes of liquid were stimulated into oscillation by the application of heat to a connecting U-tube of gas. The open U-tube of oscillating liquid thus was the source of power to do work. A linearized lossless model was proposed by Elrod<sup>3</sup> that predicted the onset of oscillation and the frequency thereof. No satisfactory physical explanation was offered for the phenomenon, however.

With the coming of the energy crisis, initial studies on reclaiming waste heat were proposed by the Harry Diamond Laboratories using the Fluidyne. With the proposed increased dependence on nuclear power, additional interest in the Fluidyne became apparent when it was conceptually demonstrated that a Fluidyne could serve as an independent power source for fluidic monitoring and control schemes that are completely decoupled from standard electromechanical systems in use. Such incidents as the Brown's Ferry fire and the loss of secondary controls could be avoided by using the residual nuclear heat to operate a self-contained Fluidyne pump and fluidic sensors and controls operating within the pressure vessel itself. A system having no moving parts except the working fluid would be extremely reliable.

The poor efficiency of currently available<sup>3</sup> pumps allows profitable operation only where the heat source costs are negligible or, as in a nuclear plant, not of concern. Improvement of the efficiency would allow greater utilization and would decrease the unit size per unit output power. This decrease would allow the use of smaller devices in such applications as nuclear power plant auxiliary control systems.

This report presents a comprehensive basis for the understanding of the Fluidyne pump's operation, analyzes the concept of the efficiency of the thermodynamic cycle, and provides important guidelines for design.

## 2. PHYSICAL DESCRIPTION OF FLUIDYNE STARTUP

In the schematic diagram (fig. 1), a reservoir of liquid is shown with a U-tube of gas connecting two liquid columns. A separate U-tube filled with the liquid is situated with one end directly beneath one end of the gas-filled tube. The other end, for this analysis, is left open to the atmosphere. The free surface motion indicates the output mechanical work available.

The gas volume may be thought to be composed of two imaginary halves. The right half, labeled "2," which connects to the output tube, is the hot side; the left half, labeled "1," is the cold side. Heat is continually applied to the right half, and the left side is maintained at a lower or ambient temperature. In the experiments conducted, the cold side was cooled by natural convection to ambient.

<sup>1</sup>C. West, *The Fluidyne Heat Engine*, United Kingdom Atomic Energy Authority, Harwell, UK, AERE-R-6775 (1971).

<sup>2</sup>C. West, *And Yet It Moves*, *New Scientist*, 29 (August 1974).

<sup>3</sup>H. Elrod, *The Fluidyne Heat Engine--How to Build One, How it Works*, National Technical Information Service, Springfield, VA, AD A006367 (1974).




Figure 1. Schematic of Fluidyne pump.

The startup and subsequent sustained oscillations may be described physically in five steps (fig. 2).




Figure 2. Schematic representation of Fluidyne startup process.

a. In equilibrium conditions, no heat is applied. The liquid levels  $h_1$ ,  $h_2$ , and  $h_5$  are prescribed by the static pressure in the gas volume of columns (1) and (2), and  $h_1 = h_2$ . (If the gas pressure  $p_{1,2}$  is ambient,  $p_{\infty}$ , then all three levels are equal.)

b. Heat is applied to the right half of the gas volume of column (2). The gas expands, and the gas volume,  $V_G$ , increases while the gas pressure  $p_{12}$  also increases. As a natural consequence, liquid levels  $h_1$  and  $h_2$  decrease, and liquid level  $h_3$  increases as the liquid in the displacer is accelerated. The gas temperature rises in column (2).

c. The inertia of the liquid in the output tube keeps the liquid moving; hence, the liquid in column (2) tends to keep moving downward, also. As more hot side is exposed, the liquid is accelerated further until equilibrium in the gas is reached.

d. Gravity stops the upward motion of liquid level  $h_1$ , and levels  $h_2$  and  $h_3$  tend to seek equality. Hence  $h_2$  increases, and  $h_3$  starts to decrease. At the same time, there is a reduction of hot volume. This reduction starts an overall gas volume decrease due to a temperature reduction since less gas is exposed to the heat source. The pressure  $p_{12}$  decreases. All this action is augmented by the descent of the output level due to gravity, which produces a dynamic head at the base of column (2), further increasing  $h_2$ . An overshoot of the two liquid levels occurs,  $h_2 > h_1$ ,  $h_2 > h_3$ . This overshoot gives rise again to a gravity potential between liquid levels.

e. The liquid levels again seek equilibrium with level  $h_2$  decreasing. This decrease exposes more of the gas to the heat source and causes the gas to expand; the cycle begins all over again, with the output liquid again moving upward.

This is the physical description as observed in a glass or plastic demonstration model built and tested during this program.

### 3. MATHEMATICAL MODEL

Geisow<sup>4</sup> has proposed a set of governing equations for a lossless Fluidyne system in an attempt to compute the conditions required for the onset of instability. To this end, he used the Euler equations of motion in one dimension, linearized them, and then performed a first-order perturbation stability analysis. The results of this analysis led to an expression for the critical temperature differential,  $\Delta T$ , as a function of the pump geometry and for the oscillating frequency,  $\omega$ . This is given as equations (1) and (1a):

$$\frac{\Delta T}{T_1 + T_2} = \frac{\rho g V_e}{2A_D P_\infty} \left( \frac{\ell_c - \ell_h}{\ell_D} \right), \quad (1)$$

$$\omega = \left[ 2g / \left( 2\ell_h + \ell_D A_c / A_D \right) \right]^{1/2}, \quad (1a)$$

<sup>4</sup>A. D. Geisow, *The Onset of Oscillations in a Lossless Fluidyne*, United Kingdom Atomic Energy Authority, Harwell, UK, AERE-M-2840 (October 1976).



where

- $T_1$  = cold temperature (K),
- $T_2$  = hot temperature (K),
- $\rho$  = liquid density ( $\text{kg/m}^3$ ),
- $g$  = acceleration of gravity ( $\text{m/s}^2$ ),
- $V_e$  = equilibrium volume of gas ( $\text{m}^3$ ),
- $A_D$  = cross-sectional area of displacer tube ( $\text{m}^2$ ),
- $P_\infty$  = atmospheric pressure (Pa),
- $l_c$  = equilibrium length of cold leg to output (m),
- $l_h$  = equilibrium length of hot leg to output (m),
- $l_D$  = length of displacer (m),
- $A_c$  = cross-sectional area of cold leg.

This analysis was performed for the geometry shown in figure 3 and indicates a strong dependency of system response on the displacer tube.




Figure 3. Schematic of Fluidyne II used by Geisow (AERE-M-2840, October 1976).

The original Fluidyne proposed by West<sup>1</sup> and described by Elrod<sup>2</sup> did indeed have such a configuration; however, currently commercially available Fluidynes<sup>3</sup> replace the displacer tube with a fluid reservoir as shown in figures 1 and 4.

<sup>1</sup>C. West, *The Fluidyne Heat Engine*, United Kingdom Atomic Energy Authority, Harwell, UK, AERE-R-6775 (1971).

<sup>2</sup>H. Elrod, *The Fluidyne Heat Engine--How to Build One, How it Works*, National Technical Information Service, Springfield, VA, AD A006367 (1974).

<sup>3</sup>*Stirling-Cycle Engines Developed at Harwell--The Fluidyne 3 Pump*, United Kingdom Atomic Energy Authority, Harwell, UK, Harwell Design Studios 56/1975 (1975).




Figure 4. Schematic of actual Fluidyne pump (diode elements—ball valves—permit unidirectional flow).

Interestingly enough, the models shown by Elrod<sup>3</sup> always have the output tube axially in line with the hot leg as opposed to being at right angles as shown in figure 3, even when the displacer is present. This leads to the observation of section 2 that dynamic head feedback from the output to the hot leg is important in the pump operation in that the inertia of the moving fluid in the output leg preferentially acts to increase the head in the hot leg.

The following set of governing equations may be generated, assuming slug flow in all tubes for the geometry of figure 1 or 4.

The pressure drop,  $\Delta P_{ij} = P_i - P_j$ , for any tube is given by the electrical analog equation for time varying slug flow<sup>6</sup> (derived from the Euler equation):

$$\Delta P_{ij} = L_{ij} \frac{dQ_{ij}}{dt} + R_{ij} Q_{ij} + h_i \rho_L g \quad (2)$$

where

$$\begin{aligned} L_{ij} &= \text{liquid inductance (kg/m}^4\text{) between points } i \text{ and } j, = \rho_L \ell_{ij} / A_{ij}, \\ \rho_L &= \text{liquid density (kg/m}^3\text{),} \\ \ell_{ij} &= \text{tube length between } i \text{ and } j \text{ (m),} \\ A_{ij} &= \text{tube cross-sectional area (m}^2\text{),} \end{aligned}$$

<sup>3</sup>H. Elrod, *The Fluidyne Heat Engine--How to Build One, How it Works*, National Technical Information Service, Springfield, VA, AD A006367 (1974).

<sup>6</sup>J. M. Kirshner, *Fluid Amplifiers*, McGraw-Hill Book Co, New York (1967).

$Q_{ij}$  = volumetric flow rate ( $m^3/s$ ) in direction  $i$  to  $j$ ,  
 $t$  = time (s),  
 $R_{ij}$  = liquid resistance (for laminar flow  $R = 8\pi\mu\ell/A^2$ ) [ $kg/(m^4 \cdot s)$ ],  
 $\mu$  = liquid viscosity [ $kg/(m \cdot s)$ ],  
 $h_{ij}$  = liquid height (m),  
 $g$  = acceleration of gravity ( $m/s^2$ ).

Therefore, for the cold leg, between steps (a) and (c) the pressure drop is

$$p_3 - p_1 = L_{13} \frac{dQ_{31}}{dt} + R_{31}Q_{31} + h_1\rho_L g \quad (3)$$

Similarly, the hot leg pressure drop can be written when the additional total pressure feedback term is included due to the dynamic head effect of the output leg:

$$p_4 - p_2 = L_{42} \frac{dQ_{42}}{dt} + R_{42}Q_{42} + h_2\rho_L g - \frac{\rho_L}{2} K_1 \left( \frac{Q_{45}}{A_{45}} \right)^2, \quad (4)$$

where

$$K_1 = 0, Q_{45} > 0; K_1 = 1, Q_{45} < 0.$$

Finally, the output leg pressure drop is, with hot leg feedback,

$$p_4 - p_5 = L_{45} \frac{dQ_{45}}{dt} + R_{45}Q_{45} + h_5\rho_L g - \frac{\rho_L}{2} K_2 \left( \frac{Q_{42}}{A_{42}} \right)^2, \quad (5)$$

where

$$K_2 = 0, Q_{42} > 0; K_2 = 1, Q_{42} < 0.$$

The equation relating the liquid height and the volume flow rate is the constitutive equation

$$A \frac{dh}{dt} = Q \quad (6)$$

Hence, the individual time rates of height change are

$$\frac{dh_1}{dt} = \frac{Q_{31}}{A_{31}} \quad (7)$$

$$\frac{dh_2}{dt} = \frac{Q_{42}}{A_{42}} \quad (8)$$

$$\frac{dh_5}{dt} = \frac{Q_{45}}{A_{45}} \quad (9)$$

It follows, from conservation of mass of an incompressible liquid into the reservoir, that the net flow must be zero, or

$$-Q_{31} - Q_{42} - Q_{45} = 0 \quad (10)$$

Note the minus signs since each flow is assumed to be positive out of the reservoir. The pressure at the base of the cold leg is the reservoir pressure. If the output leg does not impede flow from the reservoir into it or the hot leg, then  $p_3 = p_4$ . If there is an orifice resistance, then

$$p_4 - p_3 = \frac{\rho_L Q_{31}^2}{2(A_{42} - A_{45})^2 c_d^2} \quad (11)$$

where  $c_d$  is the discharge coefficient.

For convenience of this initial analysis, consider  $p_5$  to be ambient:

$$p_5 = 101 \text{ kPa (absolute)} \quad (12)$$



We have up to this point 9 equations and 11 unknowns—namely, 5 pressures, 3 flows, and 3 heights; consequently, more equations are required.

If the assumption is made that the pressure is constant at any instant of time in the gas volume, which is a reasonable assumption considering that the process is relatively slow, the gaseous resistance of the tubing is negligible, and the head potential is likewise negligible, then another equation is available:

$$P_1 = P_2 \quad (13)$$

The gas mass must be conserved so that

$$m_1 + m_2 = \text{constant} \quad (14)$$

This equation has added two unknowns,  $m_1$  and  $m_2$ , the masses of the cold and hot sides of the gas volumes (kg), respectively; hence, there are now 11 equations and 13 unknowns. The equation of state may be written for each side of the gas volume. If it is assumed that the gas is ideal, then

$$P_1 V_1 = m_1 R T_1 \quad (15)$$

$$P_1 V_2 = m_2 R T_2 \quad (16)$$

where

$$\begin{aligned} V_1 &= \text{volume of cold gas (m}^3\text{)}, \\ V_2 &= \text{volume of hot gas (m}^3\text{)}, \\ T_1 &= \text{temperature of cold gas (K)}, \\ T_2 &= \text{temperature of hot gas (K)}, \\ R &= \text{gas constant [m}^3\text{/(s}^2\text{K)}]}. \end{aligned}$$

There are now 13 equations and 17 unknowns, the new unknowns being volumes  $V_1$  and  $V_2$  and temperatures  $T_1$  and  $T_2$ .

The gas volumes are directly related geometrically to the position of the gas-liquid interface so that

$$V_1 = \frac{1}{2} V_e - (h_1 - h_e) A_{13} \quad (17)$$

and

$$v_2 = \frac{1}{2} v_e - (h_2 - h_e) A_{24} \quad , \quad (18)$$

where

$$h_e = \text{equilibrium height of liquid (m)} \quad .$$

This now brings us to 15 equations and 17 unknowns.

At this point, a statement can be made about temperatures  $T_1$  and  $T_2$ . Elrod<sup>3</sup> and Geisow<sup>4</sup> chose to assume that the temperatures are known constants. This choice is tenuous since it requires that a step distribution in temperature exists in the gas tube. For the sake of simplicity, assume that

$$T_1 = \text{constant} \quad , \quad (19)$$

$$T_2 = \text{constant} \quad , \quad (20)$$

where  $T_1$  and  $T_2$  are average temperatures (K) in each volume of gas. These then bring the count of unknowns and equations even at 17 apiece. The evaluation of  $T_1$  and  $T_2$  is given in appendix A. Upon examination of the governing equations, one notes that the pressure drop equations are nonlinear since the inductance and the resistance terms are functions of the length of the liquid, which is variable. Linearization can be achieved by stipulating that the total excursions of the liquid interfaces be considerably smaller than the equilibrium lengths. For computer solution, however, this stipulation is not necessary. There are five independent first-order ordinary differential equations, since one of the flow equations is used to find a pressure. The solution of the entire set of equations gives the displacement of the output column of liquid. Since the object of this study is to establish the parameters relating to the efficiency of the pump, a quantity of interest is the output power,  $W$ . This is the time rate of increase of potential energy of the output or the root mean square (rms) value of the product of the flow and the dynamic head. The instantaneous power out is

$$W = \frac{1}{2} \left( \frac{Q_{45}}{A_{45}} \right)^2 Q_{45} \quad . \quad (21)$$

<sup>3</sup>H. Elrod, *The Fluidyne Heat Engine--How to Build One, How it Works*, National Technical Information Service, Springfield, VA, AD A006367 (1974).

<sup>4</sup>A. D. Geisow, *The Onset of Oscillations in a Lossless Fluidyne*, United Kingdom Atomic Energy Authority, Harwell, UK, AERE-M-2840 (October 1976).

The useful power is the rms value or

$$W_{\text{rms}} = 0.707 W_{\text{max}} \quad (22)$$

The input energy is the heat input from which the temperature distribution was obtained (app A).

Physical observations indicate that most of the losses occur in the input of heat to the system.

Equations (3) to (20) may now be cast into a computer program and solved simultaneously without resorting to perturbation or threshold analyses. This simultaneity is important because the actual values of displacements are needed to compute the output power.

#### 4. NUMERICAL RESULTS

The computer program is given in appendix B with a sample printout. Figures 5 to 8 plot the various parameters of interest for typical geometries in which oscillations are self-sustained.

In figure 5, the three liquid displacements, the gas pressure, and the change of gas volume are shown as a function of time. They are in substantial agreement with the descriptive model




Figure 5. Time history of Fluidyne response:  $L_o$  = liquid inductance output,  $V_e$  = volume equilibrium,  $A_o$  = output area,  $T_2$  = temperature of hot side of gas-liquid interface, and  $h$  = height of liquid.

proposed as a result of physical observations. Constant temperature apparently causes the oscillations to keep growing. For limit cycling, a more comprehensive, flow dependent temperature distribution has to be developed that in effect provides a time delay in the temperature change. The heat conduction time constant for air is  $\tau = \rho c_p r^2 / k \approx 7$  s, where  $c_p$  = specific heat at constant pressure ( $\text{W} \cdot \text{s} / \text{kgK}$ ),  $r$  = radius of the pipe (m), and  $k$  = thermal conductivity ( $\text{W} / \text{mK}$ ). Hence, it is a poor assumption that the temperature reaches the hot or cold value instantaneously, especially since the period of oscillations is an order of magnitude less than 7.0 s. Similarly, the convective time constant due to the movement of the gas-liquid interface must be of the same order, that is, 1 s. Due to the complexity of the fluid mechanic-heat transfer governing equations for such a phenomenon, this development must be left to a more comprehensive and detailed analysis at a later time.

In figure 6, one sees the variation of amplitude and frequency of oscillation for different parametric changes. If one observes the lower three sets of curves, the effect of increasing the output length can be seen. As one would expect, the period increases with output length due to increased inductance.




Figure 6. Output displacements for various parameters:  $L_0$  = liquid inertance output,  $T_2$  = temperature of hot side of gas-liquid interface,  $V_e$  = volume equilibrium, and  $A_0$  = output area.



The middle set of curves demonstrates the effect of increasing the hot side temperature. The frequency decreases slightly with increasing temperature. This decrease is a result of the higher mean pressure in the gas volume that results in a larger volume and, hence, a slightly increased gas capacitance. Interestingly, the amplitude appears to have a maximum at a midrange temperature.

The curve marked "305" shows the effect of increasing the output area. This increase has the effect of decreasing the inductance, again increasing the frequency.

The top curve of figure 6 shows the effect of increasing the initial gas volume and the mass. The gas volume, as already suspected, acts as a capacitance; hence, increasing the capacitance decreases the frequency, as demonstrated in the figure.

Intuitively, one would expect that the predominant frequency determining terms are the output inductance and the gas capacitance. This would lead to the assumption that the system frequency,  $f$ , should behave approximately as an RLC circuit, so that

$$f = \frac{1}{2\pi(L_O C_G)^{1/2}} \quad (23)$$

where

$$C_G = \text{gas capacitance} = V_e / p_\infty \quad (\text{m}^4 \text{s}^2 / \text{kg}) \quad ,$$

$$p_\infty = \text{equilibrium absolute gas pressure (Pa)} \quad .$$

Table I shows the comparison of the frequencies from equation (23) with the actual numerical results obtained from the curves in figure 6.

**TABLE I. COMPARISON OF NUMERICALLY COMPUTED FLUIDYNE FREQUENCY WITH EQUATION (23)**

| Parameter         |   |  | Frequency (Hz) |         | Case No. |
|-------------------|---|--|----------------|---------|----------|
| Output length (m) | Gas volume ( $\times 10^{-5} \text{ m}^3$ ) | Output area ( $\times 10^{-4} \text{ m}^2$ ) | Numerical      | Eq (23) |          |
| 2.0               | 2.0   | 1.0  | 2.50           | 2.5299  | 1        |
| 7.0               | 2.0   | 1.0  | 1.54           | 1.3520  | 2        |
| 20.0              | 2.0   | 1.0  | 0.77           | 0.7997  | 3        |
| 2.0               | 4.0   | 1.0  | 1.74           | 1.7883  | 4        |
| 2.0               | 2.0   | 2.0  | 3.33           | 3.5766  | 5        |

Note: Liquid density  $\rho_L = 1000 \text{ kg/m}^3$ ; ambient absolute pressure  $p_\infty = 101 \text{ kPa}$ .

The agreement is good, so equation (23) may be used as a design guide for determining the operating frequency of a Fluidyne.

The question of cycle efficiency can be answered only by determining the nature of the thermodynamic cycle, the energy input, and the energy output. In figure 7, the relation between gas pressure and volume is shown for startup and the first cycle for case 1 of table I. It is immediately apparent that this is not a Stirling cycle as originally thought by the inventor.<sup>1</sup> Instead, it




Figure 7. Pressure-volume diagram for first cycle of Fluidyne:  $L_0$  = liquid inertance output,  $T_2$  = temperature of hot side of gas-liquid interface,  $V_e$  = volume equilibrium, and  $A_0$  = output area.

$$\begin{aligned} \text{AREA} &= pV \frac{10.5}{2} \times 0.1 \sim 0.525 \text{ m}^2 \\ \frac{2 \text{ kPa} \times 0.5 \times 10^{-6} \text{ m}^3}{\text{m}^2} &= 10^{-6} \frac{\text{kPa m}^3}{\text{m}^2} \times 10^3 \frac{\text{Pa}}{\text{kPa}} \\ &= 10^{-3} \frac{\text{Pa m}^3}{\text{m}^2} \\ pV &= 0.525 \times 10^{-3} \text{ Pa m}^3 \\ \tau &= 1/f = 0.4 \text{ s} \\ \text{WORK} &= 1.3125 \times 10^{-3} \text{ W} \\ \text{TIME} &= 1.3125 \times 10^{-3} \text{ W} \\ \text{RMS OUTPUT POWER FIRST CYCLE} &= \left( \frac{0.332 + 0.122}{2} \right) \times 10^{-3} \text{ W} \times 0.707 \\ \therefore \eta &= 12.36\% \end{aligned}$$

resembles more a Carnot cycle, albeit it is not that, either. The observed efficiency of the Fluidyne's first cycle is 12.36 percent when defined as the output power divided by the power of one cycle ( $\int p dV$ ). The heat input to the gas gives the overall efficiency. The heat input may be approximated by the convective heat transfer equation and the mean gas temperature  $\bar{T}_h$  as computed in appendix A:

<sup>1</sup>C. West, *The Fluidyne Heat Engine*, United Kingdom Atomic Energy Authority, Harwell, UK, AERE-R-6775 (1971).

$$Q_{in} = HA(T_h - \bar{T}_h) \quad , \quad (24)$$

where

$H$  = convective heat transfer coefficient ( $W/K/m^2$ ),

$A$  = outside area of hot volume =  $2\pi r l_G$  ( $m^2$ ),

$T_h$  = applied hot temperature (K) .

For the case in question, the average gas temperature  $\bar{T}_h$  for an applied temperature  $T_h = 315$  K is 313.454 K. An average value of  $H = 17$  W/K/m<sup>2</sup>, and the gas hot side area is  $3.77 \times 10^{-3}$  m<sup>2</sup>. These values result in a heat input of 0.21 W and, consequently, a poor efficiency overall. When the pump is allowed to operate for three cycles, whereupon it is expected that almost steady-state conditions would normally have been reached, the overall efficiency is up to 1.2 percent. The third-cycle efficiency is shown as a function of the applied differential temperature in figure 8. For  $L_o = 2.0$  m, there is a maximum at a differential temperature of about 24 K. This maximum could have been predicted by the observations from figure 6, where it was shown that the amplitude of oscillation was lower at elevated temperatures.




Figure 8. Fluidyne efficiency as function of input temperature and output length:  $h$  = height of liquid column and  $L_o$  = liquid inertance output.

Also, it can be observed in figure 6 that the amplitude of oscillation was inversely proportional to the output length; therefore, it seems intuitive that the efficiency increases if the output length decreases. When the gas volume increases, the amplitude also increases, but the frequency decreases. The efficiency may increase; however, since the frequency is lower, the output flow is lower, so the net effect is that the efficiency is not materially affected. Computed results (not shown here) bear out this thesis. Figure 8 shows, however, that efficiency is markedly improved by decreasing the output length. Also shown is that the optimum differential temperature is lowered by a factor of two as the maximum efficiency is more than doubled.

## 5. DISCUSSION AND CONCLUSIONS

The disturbing point in this analysis is the exponential growth of oscillations. Appendix A discusses this growth and the temperature distribution. More fundamentally, however, the reason for this growth is probably the assumption that the gas changes temperature instantaneously from hot to cold or vice versa. It takes an infinite amount of power or energy to raise a finite amount of mass a finite temperature in zero time. In a numerical model, this infinity is tempered, but still remains large. The conclusion to be drawn, therefore, is that the gas must be much more carefully modeled.

The values of efficiency presented here cannot be used in anything more than a comparative sense since they are based on output power values that are steadily increasing. Observations, however, have indicated that the actual process reaches a steady state after about three cycles. Since the frequencies computed are close to those observed and the amplitudes are reasonable, the three-cycle numerical results have been used.

Two efficiencies are involved, thermodynamic and mechanical. Thermodynamic efficiency is relatively low, and mechanical efficiency, although an order of magnitude greater than thermodynamic, is still only about 10 percent. Thus, the low efficiencies reported are substantiated by this numerical analysis. There is hope, however, of improving the overall efficiency by a factor of two or even three over the extant devices by a thorough parametric study. This study has examined more than 2500 permutations of geometry, and they cannot be presented here. The important observations, however, have been presented, and hope for better efficiency is offered.

Several conclusions may be drawn from this study. The Fluidyne pump operates not, as first thought, on a Stirling cycle, but on a cycle more closely resembling a Carnot cycle. It is essentially a low-efficiency device, although overall thermal efficiencies of 10 percent may conceivably be reached. Poor thermal coupling with the gas accounts for a large portion of this inefficiency. In the real device, it would be advantageous to have a nonconducting liquid and a highly conducting gas (a contradiction of thermodynamic terms). This advantage could possibly be realized by providing an insulating interface substance such as foam. The gas volume should be insulated so that all the heat input stays in the gas.

Relating to the analysis itself, the important points and parameters have been identified. The displacer of the original Fluidyne has been shown to be superfluous to the device. Although amplitude oscillations were never constant, limit cycling might occur when the temperature distribution is corrected or modeled more appropriately. A simple model for the frequency of the



Fluidyne has been proposed that relates the gas volume to the geometry of the output tube in terms of an electrical RLC second-order system analogy. Good agreement with numerical results has been demonstrated.

The overall objectives of this study were to determine if the efficiency of existing Fluidynes could be increased and to comprehensively describe the physics of the Fluidyne operation. These objectives have been met. The efficiency may be increased by appropriate geometric choices, and for the first time a clear description has been proposed for the operation.

Research and development of the Fluidyne heat engine should continue. The Fluidyne can provide fluid power with tiny temperature differentials, with no moving parts. For power production in inaccessible locations, this device is ideal. One of the most inaccessible places is the interior core of the pressure vessel of a nuclear reactor. The nuclear community requires redundant and completely independent safety, monitoring, and control systems. Presently, all backup controls depend on a single type of energy source—electricity. Should this ever fail, then no systems other than the purely mechanical ones could operate. The mechanical systems normally can provide only shutdown capability. A fluidic system, self-contained within the reactor core, with no pressure vessel penetrations, powered by the rectified output of a Fluidyne can provide all the active monitoring and control of the standard systems and also cause shutdown in the event of a scram. This approach can avoid the costly and inconvenient automatic shutdowns presently envisioned. A reactor may continue to operate with the fluidic system installed.

Recent panel discussions sponsored by the American Society of Mechanical Engineers (ASME)\* on fluidics and nuclear engineering specifically mentioned fluidic shutdown schemes being developed in the United States. At the same session, fluidic two-diode pumping systems were described that have been developed for the United Kingdom Atomic Energy Authority. These fluidic diode systems have successfully operated with Fluidyne pumps at Harwell. C. F. King of the University College, Cardiff, UK, reported that newly developed vortex diodes that have turndown ratios in excess of 30:1 operate exceptionally well when attached to the Fluidynes. For a session on energetics, fluidic temperature sensors that can withstand extremely hot, harsh environments were reported by Drzewiecki et al.<sup>7</sup> Such sensors are ideal candidates for use with a Fluidyne system for the monitoring of nuclear, fossil fuel, solar, and geothermal power generation plants. Of particular interest are military nuclear power facilities. These are normally mobile and do not have a ready source of auxiliary power to operate secondary systems. Even when they do, the proximity of such auxiliary systems makes them vulnerable to failure due to either the military environment or the radiation possibility from the primary plant itself. The Fluidyne offers a unique solution to this problem. It merely becomes an integral part of the whole.

---

\*T. M. Drzewiecki, *Fluidic Applications in Nuclear Engineering*, ASME Winter Annual Meeting, Atlanta, GA (November 1977).

<sup>7</sup>T. M. Drzewiecki, R. M. Phillippi, and C. Paras, *Fluidics--A New Potential for Energy Conservation by Continuous High Temperature Monitoring and Control*, Heat Transfer in Energy Conservation, R. J. Goldstein et al., ed., ASME Book H00106, New York (November 1977), 127-134.

Other military applications for remotely powered fluidic systems are battlefield security and sensor systems (REMBASS). Fluidic sensors have been demonstrated to be uniquely suited to the battlefield. The source of power has been of concern, however. A Fluidyne that can operate on a 3- or 4-deg temperature difference could operate during the day on light energy and during the night on the stored heat in the ground with the colder night air being the thermal sink. This discussion is limited only by imagination. It is the author's opinion that many military systems problems can be effectively and efficiently solved by fluidic, flueric, or fluid systems powered by Fluidyne pumps.

### LITERATURE CITED

- (1) C. West, The Fluidyne Heat Engine, United Kingdom Atomic Energy Authority, Harwell, UK, AERE-R-6775 (1971).
- (2) C. West, And Yet It Moves, New Scientist, 29 (August 1974).
- (3) H. Elrod, The Fluidyne Heat Engine--How to Build One, How it Works, National Technical Information Service, Springfield, VA, AD A006367 (1974).
- (4) A. D. Geisow, The Onset of Oscillations in a Lossless Fluidyne, United Kingdom Atomic Energy Authority, Harwell, UK, AERE-M-2840 (October 1976).
- (5) Stirling-Cycle Engines Developed at Harwell--The Fluidyne 3 Pump, United Kingdom Atomic Energy Authority, Harwell, UK, Harwell Design Studios 56/1975 (1975).
- (6) J. M. Kirshner, Fluid Amplifiers, McGraw-Hill Book Co, New York (1967).
- (7) T. M. Drzewiecki, R. M. Phillippi, and C. Paras, Fluidics--A New Potential for Energy Conservation by Continuous High Temperature Monitoring and Control, Heat Transfer in Energy Conservation, R. J. Goldstein et al, ed., ASME Book H00106, New York (November 1977), 127-134.

## NOMENCLATURE

|           |   |
|-----------|---|
| A         | area ( $\text{m}^2$ )   |
| $c_d$     | discharge coefficient (-)   |
| $c_p$     | specific heat at constant pressure ( $\text{W}\cdot\text{s}/\text{kgK}$ ) |
| C         | capacitance ( $\text{m}^4\text{s}^2/\text{kg}$ )                          |
| f         | frequency (Hz)  |
| g         | acceleration of gravity ( $\text{m}/\text{s}^2$ )                         |
| h         | height of liquid column (m)   |
| H         | convective heat transfer coefficient ( $\text{W}/\text{K}/\text{m}^2$ )   |
| k         | thermal conductivity ( $\text{W}/\text{mK}$ )                             |
| K         | constant, =1 when $Q < 0$ ; =0 when $Q > 0$                               |
| $l$       | column length (m)   |
| L         | liquid inertance (inductance) ( $\text{kg}/\text{m}^4$ )                  |
| m         | mass (kg)   |
| p         | absolute pressure (Pa)  |
| P         | pressure (Pa)   |
| Q         | volumetric flow rate ( $\text{m}^3/\text{s}$ )                            |
| r         | radius of pipe (m)  |
| R         | liquid resistance [ $\text{kg}/(\text{m}^4\cdot\text{s})$ ]               |
| $R$       | gas constant [ $\text{m}^3/(\text{s}^2\text{K})$ ]                        |
| t         | time (s)  |
| T         | absolute temperature (K)  |
| $\bar{T}$ | mean gas temperature  |
| u         | liquid velocity ( $\text{m}/\text{s}$ )                                   |
| V         | volume ( $\text{m}^3$ )   |
| W         | power (W)   |
| $\Delta$  | change  |
| $\mu$     | fluid absolute viscosity [ $\text{kg}/(\text{m}\cdot\text{s})$ ]          |
| $\eta$    | efficiency  |
| $\rho$    | liquid density ( $\text{kg}/\text{m}^3$ )                                 |
| $\tau$    | time constant (s)   |
| $\omega$  | radian oscillating frequency (rad/s)                                      |



### Subscripts

|          |  |
|----------|--|
| c        | cold   |
| D        | displacer  |
| e        | equilibrium  |
| G        | gas  |
| h        | hot  |
| i        | integer  |
| in       | input  |
| j        | integer  |
| L        | liquid   |
| max      | maximum  |
| o        | output   |
| rms      | root mean square average                                 |
| 1        | cold side of gas-liquid interface                        |
| 2        | hot side of gas-liquid interface                         |
| 3        | cold side of tube lower end                              |
| 4        | hot side of tube lower end, entrance to output tube node |
| 5        | output tube exit   |
| $\infty$ | ambient, atmospheric                                     |

**APPENDIX A.--TEMPERATURE DISTRIBUTION  
IN AN ENCLOSED CYLINDRICAL GAS VOLUME**

## APPENDIX A

The gas volume that provides the means for the motive power in the Fluidyne is essentially cylindrical. It is bounded on either end by liquid interfaces that move so that the volume of gas expands and contracts. Heat is applied to one half and rejected from the other half by maintaining essentially constant hot and cold wall temperatures,  $T_h$  and  $T_c$ , respectively. Consider, therefore, two touching cylinders with constant wall and end temperatures. The end temperatures can be justified to be  $T_h$  or  $T_c$  if the conductivity of the liquid is much greater than that of the gas. Figure A-1 shows the assumed geometry.




Figure A-1. Schematic of gas volume.

Assume one-dimensional heat flow in the  $x$ -direction, and further assume that heat enters the volume by natural convection from the wall temperatures. In the first instance, neglect any motion of the interfaces, and compute the static temperature distribution. For an infinitesimal slice of the volume of length  $dx$ , the heat balance is shown in figure A-2.




Figure A-2. Heat balance in differential element.

## APPENDIX A

The heat balance is

$$q_x - \left( q_x + \frac{dq_x}{dx} dx \right) + q = 0 , \quad (A-1)$$

where

$$q_x = \text{heat conducted in x-direction} = -k\pi r^2 dT/dx ,$$

$$q = \text{heat convected into gas} = H2\pi r dx (T_h - T) ,$$

$$k = \text{thermal conductivity (W/mK)} ,$$

$$r = \text{radius of pipe (m)} ,$$

$$H = \text{convective heat transfer coefficient (W/K/m}^2\text{)} .$$

The governing differential equations for the hot and cold columns are

$$\frac{d^2T}{dx^2} + \frac{2H}{kr} (T_h - T) = 0 , \quad (A-2)$$

$$\frac{d^2T}{dx^2} + \frac{2H}{kr} (T_c - T) = 0 . \quad (A-3)$$

A new temperature parameter is defined as

$$\theta_h = T - T_h , \quad (A-4)$$

$$\theta_c = T - T_c . \quad (A-5)$$

In addition, define a length parameter for the cold side,

$$y = (\ell_c + \ell_h) - x , \quad (A-6)$$

and let

$$\lambda^2 = 2H/kr . \quad (A-7)$$



## APPENDIX A

The governing equations thus become

$$\frac{d^2 \theta_h}{dx^2} - \lambda^2 \theta_h = 0 , \quad (A-8)$$

$$\frac{d^2 \theta_c}{dy^2} - \lambda^2 \theta_c = 0 . \quad (A-9)$$

The solutions of equations (A-4) to (A-9) are

$$\theta_h(x) = B_1 \sinh \lambda x + B_2 \cosh \lambda x , \quad (A-10)$$

$$\theta_c(y) = B_3 \sinh \lambda y + B_4 \cosh \lambda y . \quad (A-11)$$

The boundary conditions are

$$T(x=0) = T_h ,$$

$$T(x=l_c+l_h) = T_c ,$$

$$T_h(x=l_h) = T_c(x=l_h) ,$$

$$\frac{dT_h(x=l_h)}{dx} = \frac{dT_c(x=l_h)}{dx} .$$

In terms of the new parameters,

$$\theta_h(0) = 0 , \quad (A-12)$$

$$\theta_h(l_h) = \theta_c(l_c) + T_c - T_h , \quad (A-13)$$

$$\frac{d\theta_h}{dx}(l_h) = - \frac{d\theta_c}{dy}(l_c) , \quad (A-14)$$

$$\theta_c(0) = 0 . \quad (A-15)$$

## APPENDIX A

Equations (A-12) and (A-15) make  $B_2 = B_4 = 0$ . If now  $\ell_c$  is assumed equal to  $\ell_h$  (on the average), then by symmetry equations (A-13) and (A-14) may be replaced if

$$T(x=\ell_h) = \frac{T_h + T_c}{2} .$$

Thus,

$$\theta_h(\ell_h) = \frac{T_c - T_h}{2}$$

and

$$\theta_c(\ell_c) = \frac{T_h - T_c}{2} ,$$

so that

$$\theta_h(x) = \frac{(T_c - T_h) \sinh \lambda x}{2 \sinh \lambda \ell_h} , \quad (A-16)$$

$$\theta_c(y) = \frac{(T_h - T_c) \sinh \lambda y}{2 \sinh \lambda \ell_c} . \quad (A-17)$$

For the analysis, average values may be used so that

$$\bar{T}_h = T_h + \frac{1}{\ell_h} \int_0^{\ell_h} \theta_h(x) dx$$

and

$$\bar{T}_c = T_c + \frac{1}{\ell_c} \int_0^{\ell_c} \theta_c(y) dy .$$

## APPENDIX A

When equations (A-16) and (A-17) are substituted and the indicated integrations are performed, the results are

$$\bar{T}_h = T_h + \frac{T_c - T_h}{2\lambda \ell_h \sinh \lambda \ell_h} (\cosh \lambda \ell_h - 1) \quad (A-18)$$

and

$$\bar{T}_c = T_c + \frac{T_h - T_c}{2\lambda \ell_c \sinh \lambda \ell_c} (\cosh \lambda \ell_c - 1) \quad (A-19)$$

These average temperatures are used in the numerical model.

A more sophisticated model assumes that the hot side liquid is asymptotically cold. In this model, there are three temperature zones. The formulation is the same for equations (A-18) and (A-19), except that the simplifying assumption of symmetry is not used. The solutions only are given here:

$$\begin{aligned} T_L(x) &= B_1 e^{\lambda_L x} + T_c, \\ T_h(x) &= B_1 \frac{\lambda_L}{\lambda_G} \sinh \lambda_G x + (B_1 + T_c - T_h) \cosh \lambda_G x + T_h, \\ T_c(x) &= B_5 \sinh [\lambda_G (\ell_c + \ell_h - x)] + T_c, \\ B_1 &= \frac{1}{B} (T_h - T_c) \left[ \cosh \lambda_G \ell_h - 1 + \tanh (\lambda_G \ell_c) \sinh \lambda_G \ell_h \right], \\ B &= \frac{\lambda_L}{\lambda_G} \sinh \lambda_G \ell_h + \cosh \lambda_G \ell_h + \frac{1}{\lambda_G} \tanh \lambda_G \ell_c (\lambda_L \cosh \lambda_G \ell_h + \lambda_G \sinh \lambda_G \ell_h), \\ B_5 &= \frac{B_1 \left( \frac{\lambda_L}{\lambda_G} \sinh \lambda_G \ell_h + \cosh \lambda_G \ell_h \right) + (T_c - T_h) (\cosh \lambda_G \ell_h - 1)}{\sinh \lambda_G \ell_c}, \end{aligned}$$

and the average hot and cold temperatures are

$$\begin{aligned} \bar{T}_h &= T_h + \frac{B_1 \lambda_L}{\lambda_G^2 \ell_h} (\cosh \lambda_G \ell_h - 1) + \frac{B_1 + T_c - T_h}{\lambda_G \ell_h} \sinh \lambda_G \ell_h, \\ \bar{T}_c &= T_c + \frac{B_5}{\lambda_G \ell_c} (\cosh \lambda_G \ell_c - 1), \end{aligned}$$

## APPENDIX A

where

$T_L$  = temperature of liquid ,

$G$  = gas ,

$\ell_c$  = length of cold column ,

$\ell_h$  = length of hot column ,

$B_i$  = constant of integration .

Even more sophistication may be introduced by dropping the one-dimensional restriction. Dropping it leads to two governing equations,

$$\frac{\partial^2 \theta_i}{\partial \xi^2} + \left( \frac{\ell_h + \ell_c}{R} \right)^2 \frac{\partial^2 \theta_i}{\partial \psi^2} + \left( \frac{\ell_h + \ell_c}{R} \right)^2 \frac{1}{\psi} \frac{\partial \theta_i}{\partial \psi} = 0 ,$$

where

$$\theta_i = \frac{T - T_c}{T_h - T_c} ,$$

$$\xi = x / (\ell_h + \ell_c) ,$$

$R$  = liquid resistance,

$$\psi = r/R ,$$

$$i = L, G ,$$

with these boundary conditions on the liquid:

$$\theta_L(\xi, 1) = 0 ,$$

$$\theta_L(-\infty, \psi) = 0 ,$$

$$\frac{\partial \theta_L}{\partial \psi}(\xi, 0) = 0 ,$$

$$\theta_L(0, \psi) = \theta_G(0, \psi) ;$$



and with these boundary conditions on the gas:

$$\theta_G(\xi, 1) = \begin{cases} 1, & 0 \leq \xi < \ell_h / (\ell_h + \ell_c) \\ 0, & \xi \geq \ell_h / (\ell_h + \ell_c) \end{cases},$$

$$\frac{\partial \theta_G}{\partial \psi}(\xi, 0) = 0,$$

$$\frac{\partial \theta_G}{\partial \xi}(0, \psi) = \frac{\partial \theta_L}{\partial \xi}(0, \psi),$$

$$\theta_G(1, \psi) = 0.$$

These equations may be solved by separation of variables and lead to two eigenvalue problems resulting in a double infinite series in hyperbolic functions and Bessel functions. This tedious solution is left for the reader if he should desire to pursue it.

The original differential equations (A-2) and (A-3) are altered when gaseous motion is considered. Equation (A-3) becomes

$$\frac{d^2 T}{dx^2} + \frac{2H}{Rk} (T_h - T) - \frac{\psi_c u}{k} \frac{dT}{dx} = 0, \quad (A-20)$$

where  $u$  = liquid viscosity. If one assumes that the initial static temperature distribution is developed prior to any volume change (gas velocity onset), equation (A-20) may be used to examine the relative importance of the convective and conductive terms. Assume that a temperature distribution exists. Assign order of magnitude values to the derivatives:

$$\frac{dT}{dx} \sim \frac{T_h - T_c}{\ell_h},$$

$$\frac{d^2 T}{dx^2} \sim \frac{T_h - T_c}{\ell_h^2}.$$

For the conductive term  $d^2 T/dx^2$  to be negligible compared with the convective term  $(\psi_c u/k) dT/dx$ ,

$$\frac{d^2 T}{dx^2} \ll \frac{\psi_c u}{k} \frac{dT}{dx},$$

## APPENDIX A

or

$$\frac{\psi_c u \ell_h}{k} \gg 1 \quad . \quad (A-21)$$

For air,

$$\psi = 1.2 \text{ kg/m}^3 ,$$

$$c_p = 1.05 \times 10^3 \text{ W}\cdot\text{s/kgK}, \text{ specific heat at constant pressure,}$$

$$\ell_h = 0.1 \text{ m} ,$$

$$k = 0.026 \text{ W/mK}, \text{ thermal conductivity .}$$

For the velocity, assume sinusoidal displacement of  $\pm 0.02 \text{ m}$  at  $3 \text{ Hz}$ , so that the maximum velocity is  $2\pi f(0.02) = 0.38 \text{ m/s}$ . Therefore,

$$\frac{\psi_c u \ell_h}{k} = 1841 \gg 1 \quad .$$

This indicates that during oscillation there is no significant effect of conduction; consequently, if the gas volume moves back and forth as a slug, the temperature is governed only by

$$\frac{d\theta}{dx} + \frac{\psi_c u R}{2H} \theta = 0 \quad ,$$

which implies that

$$\theta = B_6 \exp\left(-\frac{\psi_c u R}{2H} x\right) \quad ,$$

and if the boundary condition is that  $\theta = 0$ , then  $B_6 = 0$ , and the temperature remains at its initial constant value.

In reality, the volume expands and contracts, and there is conduction with a lag time, so that the initial temperature distribution eventually decays to a more uniform overall temperature due to the mixing effect of the convective terms. In addition, more complex boundary conditions exist. A thermal lag through the wall or the device supplies heat, and there is conduction axially in the walls. A considerable effort would have to be expended to thoroughly analyze the complete problem, given the velocity distribution. If we add now the complexity of coupling the transient

## APPENDIX A

three-dimensional energy equation and the Navier-Stokes equations for the gas to the time-dependent oscillating liquid equations, the problem becomes massive.

A tentative time to solve such a problem is 1 to 2 man years. Such a solution would be highly desirable if any great effort or expenditure were ever contemplated for the Fluidyne.

**APPENDIX B.--COMPUTER PROGRAM AND NUMERICAL RESULTS**



## APPENDIX B

This appendix presents the Fluidyne pump computer program written in FORTRAN IV for a 360/70 IBM computer. Five first-order differential equations are integrated by DVERK, an IBM supplied Runge-Kutta scheme that uses a fifth- and a sixth-order algorithm to reduce the global error to that specified by the user. It chooses the time increments within the desired steps of printout, which are specified by XEND. The program has five nested parameter DO loops that compute the response of the Fluidyne while the following parameters are swept:

- Output length
- Equilibrium liquid height
- Equilibrium gas volume
- Output area
- Maximum hot temperature

All units are specified in SI units, except for the gas constant, which is in English customary units, but is converted in the program. All outputs are in SI units.

A sample printout is given for case 1 of table I in the main body of the report.

# APPENDIX B

01/04/78 12.12.17

FILE: FLUDYN FORTRAN P1

NAVAL POSTGRADUATE SCHOOL

```

C THE PROGRAM FLUDYN SOLVES THE GOVERNING EQUATIONS FOR THE FLUIDYNE 3
C PUMP AS FORMULATED BY T. OKZEWIECKI ON 27 SEP 1977
      DIMENSION Y(5),C(24),W(5,9)
      DIMENSION YPRIME(5)
      COMMON P4,P5,R45,RHOLIQ,G,A24,H45,P3,P1,R31,H13,A13,A45
      EXTERNAL FCN
C INPUT PARAMETERS: COLD TEMPERATURE,K; TEMPERATURE INCREMENT,K;
C EQUILIBRIUM HEIGHTS,M;EQUILIBRIUM GAS VOLUME,M3;AMBIENT PRESSURE,KPA;
C COLD LEG AREA,M2;HOT LEG AREA,M2;OUTPUT LEG AREA,M2;COLD LEG LENGTH,M;
C HOT LEG LENGTH,M;OUTPUT LEG LENGTH,M;LIQUID DENSITY,KG/M3;
C GAS CONSTANT,FT-LBF/LBM-F;PI;LIQUID VISCOSITY,KG/M/S;MAXIMUM HOT LEG
C TEMPERATURE,K;GRAVITATIONAL CONSTANT,M2/S;TIME INCREMENT,S.
      READ(5,50) T1,DELT,HE,VE,P5,A13,A24,A45,HC,HH,H0,RHOLIQ
      READ(5,51) R,PI,VIS,TMAX,G,DT
      READ(5,52) K1
      P5=P5*1000.
      R=R*2.205*1.8*6.85*12000.*(0.0254**3)
      DO 60 JHC=1,10
      HC=FLCAT(JHC)
      WRITE(6,200) HO
200  FCNMT(' HO=',F7.1)
      DO 61 JHE=1,4
      HE=.1*FLOAT(JHE)
      WRITE(6,201) HE
201  FCNMT(' HE=',F7.2)
      DO 62 JVE=1,4
      VE=.0001*FLCAT(JVE)
      WRITE(6,202) VE
202  FCNMT(' VE=',F5.5)
      DO 63 JA45=1,3
      A45=.001*FLOAT(JA45)
      WRITE(6,203) A45
203  FCNMT(' A45=',F9.5)
      DO 64 JTMAX=1,6
      TMAX=295+.1C*FLCAT(JTMAX)
      WRITE(6,204) TMAX
204  FCNMT(' TMAX=',F7.1)
      N=5
C INITIAL CONDITIONS
      X=C.C
      Y(1)=C.C
      Y(2)=0.0
      Y(3)=HE
      Y(4)=HE
      Y(5)=HE
      T2=T1
      C=158.*VE/A24
      F=(COSH(C)-1.)/2./C/SINH(C)
      YP=1*Y(1)=0.0
      YP=1*Y(2)=0.0
      T2=C.CC1
      INC=1
      C=C*F5*VE/R/T1
C COMPUTATION OF RESISTANCES AND INDUCTANCES
C AND GAS LOSS.
      WRITE(5,55)
      WRITE(5,56)
      DO 10 K=1,K1
      R31=.5*PI*VIS*Y(3)/A13**2
      R24=.5*PI*VIS*Y(4)/A24**2
      R45=.5*PI*VIS*(HO-HE+Y(5))/A45**2
      H13=RHOLIQ*Y(3)/A13
      H24=RHOLIQ*Y(4)/A24
      H45=RHOLIQ*(HO-HE+Y(5))/A45
C START COMPUTATION OF TIME VARYING SEQUENCE AND INTEGRATION OF THE DE
      XEND=FLCAT(K)*DT
      V1=VE/2.-(Y(3)-HE)*A13
      V2=VE/2.-(Y(4)-HE)*A24
      V=V1+V2

```

THIS PAGE IS BEST QUALITY PRACTICABLE  
FROM COPY FURNISHED TO DDC

## APPENDIX B

FILE: FLUDYN FORTRAN P1

NAVAL POSTGRADUATE SCHOOL

```

TC=T1+(T2-T1)*F
TH=T2+(T1-T2)*F
P1=GMASS*R*TC*TH/(V1*TH+V2*TC)
P2=P1
IF(Y(1).GT.0.0) GO TO 6
B1=1.0
GO TO 7
6 B1=0.0
7 CONTINUE
P4=H24*(-YPRIME(1)-YPRIME(2))+P2+R24*(-Y(1)-Y(2))+R*CLIQ/2.*(Y(1)/
1 A45)**2*B1+RHOLIQ*Y(4)*G
P3=P4-R*CLIQ/.72*Y(2)*ABS(Y(2))/(A24-A45)**2
CALL DVERK(N,FCN,X,Y,XEND,TOL,IND,C,NW,W,IER)
IF(IND.LT.0.OR.IER.GT.0) GO TO 20
P6=P1/1000.
POWER=Y(1)*(Y(1)/A45)**2*RHOLIQ/2.
Y3=Y(3)-HE
Y4=Y(4)-HE
Y5=Y(5)-HE
P7=P6-P5*.001
V4=V-VE
WRITE(6,30) Y(1),POWER,Y3,Y4,Y5,X,P7,T2,V4
T2=T2+DELT
IF(T2.LT.TMAX) GO TO 10
10 T2=TMAX
CONTINUE
WRITE(6,87) TC,TH,R,D,F
WRITE(6,88)
87 FORMAT(' TC=',F8.3,' TH=',F8.3,' R=',F10.3,' D=',E10.4,' F=',E10.4)
1) FORMAT(' END OF PROGRAM')
88 CONTINUE
64 CONTINUE
63 CONTINUE
62 CONTINUE
61 CONTINUE
60 CONTINUE
STOP
50 FORMAT(12F6.0)
51 FORMAT(6F6.0)
52 FORMAT(I3)
30 FORMAT(7E12.4,F7.1,' ',E12.5)
35 FORMAT(' OUTPUT FLCW OUTPUT PCWER COLD DISPL HOT DISPL OUTPUT DI
1 SPL TIME GAS PRESSURE HCT TEMP GAS VOLUME')
36 FORMAT(' (M3/S) (WATTS) (M) (M) (M)')
1 (S) (KPA) (K) (M3) (')
20 CONTINUE
WRITE(6,40) IER,INC
40 FORMAT(2I3)
STOP
END
SUBROUTINE FCN(N,X,Y,YPRIME)
DIMENSION Y(5),YPRIME(5)
COMMON P4,P5,R45,RHOLIQ,G,A24,H45,P3,P1,R31,H13,A13,A45
IF((-Y(1)-Y(2)).GT.0.0) GO TO 11
B2=1.0
GO TO 12
11 B2=C.C
12 CONTINUE
YPRIME(1)=(P4-P5-R45*Y(1)-Y(5)*RHOLIQ*G-RHOLIQ/2.*(-Y(1)-Y(2))**2/
1 A24/A24*B2)/H45
YPRIME(2)=(P3-P1-R31*Y(2)-Y(3)*RHOLIQ*G)/H13
YPRIME(3)=Y(2)/A13
YPRIME(4)=(-Y(1)-Y(2))/A24
YPRIME(5)=Y(1)/A45
RETURN
END

```

THIS PAGE IS BEST QUALITY PRACTICABLE  
FROM COPY FURNISHED TO DDC

| TIME (S) | GAS PRESSURE (KPA) | HOT TEMP (K) | GAS VOLUME (M3) | OUTPUT DISPL (M) | HOT DISPL (M) | COLD DISPL (M) | OUTPUT POWER (WTS) | FLCM |
|----------|--------------------|--------------|-----------------|------------------|---------------|----------------|--------------------|------|
| 0.00     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.01     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.02     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.03     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.04     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.05     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.06     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.07     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.08     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.09     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.10     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.11     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.12     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.13     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.14     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.15     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.16     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.17     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.18     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.19     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.20     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.21     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.22     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.23     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.24     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.25     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.26     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.27     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.28     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.29     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.30     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.31     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.32     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.33     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.34     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.35     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.36     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.37     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.38     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.39     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.40     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.41     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.42     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.43     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.44     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           | 0.00               | 0.00 |
| 0.45     | 0.00               | 253.0        | 0.00            | 0.00             | 0.00          | 0.00           |                    |      |



# DISTRIBUTION

DEFENSE DOCUMENTATION CENTER  
CAMERON STATION, BUILDING 5  
ALEXANDRIA, VA 22314  
ATTN DDC-TCA (12 COPIES)

COMMANDER  
USA RSCH & STD GPR (EUR)  
BOX 65  
FPO NEW YORK 09510  
ATTN LTC JAMES M. KENNEDY, JR.  
CHIEF, PHYSICS & MATH BRANCH

COMMANDER  
US ARMY MATERIEL DEVELOPMENT &  
READINESS COMMAND  
5001 EISENHOWER AVENUE  
ALEXANDRIA, VA 22333  
ATTN DRXAM-TL, HQ TECH LIBRARY  
ATTN DRCRD-TP, WILLIAM RALPH  
ATTN DRCRD-TP, J. CORRIGAN

COMMANDER  
USA ARMAMENT COMMAND  
ROCK ISLAND, IL 61201  
ATTN DRSAR-ASF, FUZE DIV  
ATTN DRSAR-RDF, SYS DEV DIV - FUZES  
ATTN DRSAR-RDC-T, MR. R. SPENCER  
ATTN DRSAR-ASF  
ATTN DRSAR-LEP-L, TECH LIBRARY

COMMANDER  
USA MISSILE & MUNITIONS CENTER  
& SCHOOL  
REDSTONE ARSENAL, AL 35809  
ATTN ATSK-CTD-F

COMMANDER IDDR&E  
PENTAGON, ROOM 3D 1089  
WASHINGTON, DC 20310  
ATTN LTC G. KOPESAK

OFFICE OF THE DEPUTY CHIEF OF STAFF  
FOR RES, DEV & ACQUISITION  
DEPARTMENT OF THE ARMY  
WASHINGTON, DC 20310  
ATTN DAMA-ARP-P, DR. V. GARBER  
ATTN MR. JOHN HILL, ROOM 3D424

US ARMY R&D GROUP (EUROPE)  
BOX 15  
FPO NEW YORK 09510  
ATTN CHIEF, AERONAUTICS BRANCH  
ATTN CHIEF, ENGINEERING SCIENCES

US ARMY RESEARCH OFFICE  
P. O. BOX 12211  
RESEARCH TRIANGLE PARK, NC 27709  
ATTN JAMES J. MURRAY, ENG SCI DIV

COMMANDER  
USA FOREIGN SCIENCE & TECH CENTER  
FEDERAL OFFICE BUILDING  
220 7TH STREET, NE  
CHARLOTTESVILLE, VA 22901  
ATTN DRXST-SD1

COMMANDER  
USA MISSILE RES & DEV COMMAND  
REDSTONE ARSENAL, AL 35809  
ATTN REDSTONE SCIENTIFIC INFO  
CENTER, DRSMI-RBD  
ATTN DRDMI-TGC, WILLIAM GRIFFITH  
ATTN DRDMI-TGC, JAMES G. WILLIAMS  
ATTN DRDMI-TGC, J. C. DUNAWAY  
ATTN DRCPM-TOE, FRED J. CHEPLEN

COMMANDER  
USA MOBILITY EQUIPMENT R&D CENTER  
FORT BELVOIR, VA 22060  
ATTN TECH LIB (VAULT)  
ATTN DRDME-EM, R. N. WARE

COMMANDER  
EDGEWOOD ARSENAL  
ABERDEEN PROVING GROUND, MD 21010  
ATTN SAREA-MT-T, MR. D. PATTON

COMMANDER  
US ARMY ARRADCOM  
DOVER, NJ 07801  
ATTN SARPA-TS-S-#59  
ATTN DRDAR-LCN-F, A. E. SCHMIDLIN  
ATTN DRDAR-LCW-E, MR. J. CONNOR  
ATTN SARPA-ND-C-C, D. SAMPAR

COMMANDER  
WATERVLIET ARSENAL  
WATERVLIET ARSENAL, NY 12189  
ATTN GARY W. WOODS  
ATTN SARWV-RDT-L  
ATTN JOHN BARRETT

COMMANDER  
USA TANK AUTOMOTIVE RES & DEV CMD  
ARMOR & COMP DIV, DRDTA-RKT  
BLDG 215  
WARREN, MI 48090  
ATTN T. KOZOWYK  
ATTN M. STEELE

COMMANDER  
WHITE SANDS MISSILE RANGE  
WHITE SANDS, NM 88002  
ATTN STEWS-AD-L, TECH LIBRARY

COMMANDER  
RODMAN LABORATORIES  
ROCK ISLAND ARSENAL  
ROCK ISLAND, IL 61201  
ATTN SARRI-LA

OFFICE OF NAVAL RESEARCH  
DEPARTMENT OF THE NAVY  
ARLINGTON, VA 22217  
ATTN STANLEY W. DOROFF, CODE 438  
ATTN D. S. SIEGEL, CODE 211

DEPARTMENT OF THE NAVY  
R&D PLANS DIVISION  
ROOM 5D760, PENTAGON  
WASHINGTON, DC 20350  
ATTN BENJ R. PETRIE, JR., OP-987P4

COMMANDING OFFICER  
NAVAL AIR ENGINEERING CENTER  
LAKEHURST, NY 08733  
ATTN ESSD, CODE 9314, HAROLD OTT

NAVAL AIR SYSTEMS COMMAND  
DEPARTMENT OF THE NAVY  
WASHINGTON, DC 20360  
ATTN CODE AIR-52022A, J. BURNS  
ATTN CODE AIR-52022E, D. HOUCK

COMMANDER  
PACIFIC MISSILE RANGE  
NAVAL MISSILE CENTER  
POINT MUGU, CA 93042  
ATTN CODE 3123, ABE J. GARRETT  
ATTN CODE 1243, A. ANDERSON

COMMANDER  
NAVAL SHIP ENGINEERING CENTER  
PHILADELPHIA DIVISION  
PHILADELPHIA, PA 19112  
ATTN CODE 6772, D. KEYSER

COMMANDER  
NAVAL SURFACE WEAPONS CENTER  
WHITE OAK, MD 20910  
ATTN CODE 413, CLAYTON MCKINDRA  
ATTN CODE WA-33, J. O'STEEN  
ATTN DIV 412, C. J. SEWELL

NAVAL POSTGRADUATE SCHOOL  
MECHANICAL ENGINEERING  
MONTREY, CA 93940  
ATTN CODE 69, PROF. R. NUNN

NAVAL SHIP RES & DEV CENTER  
CODE 1619, MR. K. READER  
BETHESDA, MD 20084

NAVAL SEA SYSTEMS COMMAND  
SEA0331H  
WASHINGTON, DC 20362  
ATTN A. CHAIKIN

COMMANDER  
NAVAL WEAPONS CENTER  
CHINA LAKE, CA 93555  
ATTN CODE 533, LIBRARY DIVISION  
ATTN CODE 5536, MR. M. D. JACOBSON

COMMANDER  
AF AERO PROPULSION LAB, AFSC  
WRIGHT-PATTERSON AFB, OH 45433  
ATTN LESTER SMALL, ITBC

COMMANDER  
AIR FORCE AVIONICS LABORATORY  
WRIGHT-PATTERSON AFB, OH 45433  
ATTN RWN-2, RICHARD JACOBS

DIRECTOR  
AF OFFICE OF SCIENTIFIC RESEARCH  
1400 WILSON BLVD  
ARLINGTON, VA 22209  
ATTN NE, MR. C. KNAUSENBERGER

# DISTRIBUTION (Cont'd)

DIRECTOR  
APPLIED TECHNOLOGY LAB  
FORT EUSTIS, VA 23504  
ATTN DAVDL-EU-SYA, G. W. FOSDICK

COMMANDER  
AF WEAPONS LABORATORY, AFSC  
KIRTLAND AFB, NM 87117  
ATTN SUL, TECHNICAL LIBRARY

COMMANDER  
ARMAMENT DEV & TEST CENTER  
EGLIN AIR FORCE BASE, FL 32542  
ATTN ADTC (DLOSL), TECH LIBRARY

AIR FORCE FLIGHT TEST CENTER  
6510 ABC/SSD  
EDWARDS AFB, CA 93523  
ATTN TECHNICAL LIBRARY

4950TH TEST WING (TZHM)  
WRIGHT-PATTERSON AFB  
DAYTON, OH 45424  
ATTN MR. MICHAEL COLLINS

AF INSTITUTE OF TECHNOLOGY, AU  
WRIGHT-PATTERSON AFB, OH 45433  
ATTN LIBRARY AFFT(LD), BLDG 640,  
AREA B  
ATTN AFFT(ENM), MILTON E. FRANKE  
(3 COPIES)

AEROSPACE MEDICAL DIVISION  
BROOKS AFB, TX 78235  
ATTN AMD/RDN, CPT G. JAMES

DIV OF REACTOR RES & DEV  
F-309 US ERDA  
WASHINGTON, DC 20545  
ATTN FRANK C. LEGLER

OAK RIDGE NATIONAL LABORATORY  
CENTRAL RES LIBRARY,  
BLDG 4500N, RM 175  
P. O. BOX X  
OAK RIDGE, TN 37830  
ATTN E. HOWARD

DEPARTMENT OF COMMERCE  
BUREAU OF EAST-WEST TRADE  
OFFICE OF EXPORT ADMINISTRATION  
WASHINGTON, DC 20230  
ATTN WALTER J. RUSNACK

SCIENTIFIC LIBRARY  
US PATENT OFFICE  
WASHINGTON, DC 20231  
ATTN MRS. CURETON

DEPARTMENT OF COMMERCE  
NATIONAL BUREAU OF STANDARDS  
WASHINGTON, DC 20234  
ATTN GUSTAVE SHAPIRO, 425.00

NASA AMES RESEACH CENTER  
MOFFETT FIELD, CA 94035  
ATTN MS 244-13, DEAN CHISEL

COMMANDER  
NAVAL AIR DEVELOPMENT CENTER  
WARMINSTER, PA 18974  
ATTN R. MCGIBONEY, 30424  
ATTN CODE 8134, LOIS GUISE

NASA LEWIS RESEARCH CENTER  
21000 BROOKPARK ROAD  
CLEVELAND, OH 44135  
ATTN VERNON D. GEBBEN

NASA SCIENTIFIC & TECH INFO FACILITY  
P. O. BOX 8657  
BALTIMORE/WASHINGTON  
INTERNATIONAL AIRPORT, MD 21240  
ATTN ACQUISITIONS BRANCH

UNIVERSITY OF ALABAMA  
CIVIL & MINERAL ENGINEERING DEPT.  
P. O. BOX 1468  
UNIVERSITY, AL 35486  
ATTN DR. HAROLD R. HENRY

ARIZONA STATE UNIVERSITY  
ENGINEERING CENTER  
TEMPE, AZ 85281  
ATTN PETER K. STEIN, LABORATORY  
FOR MEASUREMENT SYS ENGR

UNIVERSITY OF ARKANSAS  
TECHNOLOGY CAMPUS  
P. O. BOX 3017  
LITTLE ROCK, AR 72203  
ATTN PAUL C. MCLEOD

UNIVERSITY OF ARKANSAS  
MECHANICAL ENGINEERING  
FAYETTEVILLE, AR 72701  
ATTN JACK H. COLE, ASSOC PROF

CARNEGIE-MELLON UNIVERSITY  
SCHENLEY PARK  
PITTSBURGH, PA 15213  
ATTN PROF W. T. ROULEAU,  
MECH ENGR DEPT

CASE WESTERN RESERVE UNIVERSITY  
UNIVERSITY CIRCLE  
CLEVELAND, OH 44106  
ATTN PROF P. A. ORNER

THE CITY COLLEGE OF THE CITY  
UNIVERSITY OF NEW YORK  
DEPT OF MECH ENGR  
139TH ST. AT CONVENT AVENUE  
NEW YORK, NY 10031  
ATTN PROF L. JIJJ  
ATTN PROF G. LOWEN

DUKE UNIVERSITY  
COLLEGE OF ENGINEERING  
DURHAM, NC 27706  
ATTN C. M. HARMAN

ENGINEERING SOCIETIES LIBRARY  
345 EAST 47TH STREET  
NEW YORK, NY 10017

COMMANDER  
AIR FORCE FLIGHT DYNAMICS LAB  
WRIGHT-PATTERSON AFB, OH 45433  
ATTN AFFDL/FGL, H. SNOWBALL

IIT RESEARCH INSTITUTE  
10 WEST 35TH STREET  
CHICAGO, IL 60616  
ATTN DR. K. E. MCKEE

LEHIGH UNIVERSITY  
DEPT. OF MECHANICAL ENGINEERING  
BETHLEHEM, PA 18015  
ATTN PROF FORBES T. BROWN

LINDA HALL LIBRARY  
5109 CHERRY STREET  
KANSAS CITY, MO 64110  
ATTN DOCUMENTS DIVISION

MASSACHUSETTS INSTITUTE  
OF TECHNOLOGY  
77 MASSACHUSETTS AVENUE  
CAMBRIDGE, MA 02139  
ATTN ENGINEERING TECHNICAL  
REPORTS, RM 10-408  
ATTN DAVID WORMLEY, MECH ENGR  
DEPT, RM 3-146

MICHIGAN TECHNOLOGICAL  
UNIVERSITY  
LIBRARY, DOCUMENTS DIVISION  
HOUGHTON, MI 49931  
ATTN J. HAWTHORNE

UNIVERSITY OF MISSISSIPPI  
201 CARRIER HALL, DEPT OF MECH ENGR  
UNIVERSITY, MS 38677  
ATTN DR. JOHN A. FOX

MISSISSIPPI STATE UNIVERSITY  
DRAWER ME  
STATE COLLEGE, MS 39672  
ATTN DR. C. J. BELL, MECH ENG DEPT

UNIVERSITY OF NEBRASKA LIBRARIES  
ACQUISITIONS DEPT, SERIALS SECTION  
LINCOLN, NE 68508  
ATTN ALAN GOULD

UNIVERSITY OF NEW HAMPSHIRE  
MECH ENGR DEPT, KINGSBURY HALL  
DURHAM, NH 03824  
ATTN PROF CHARLES TATE (3 COPIES)

DEPT OF MECHANICAL ENGINEERING  
NEWARK COLLEGE OF ENGINEERING  
323 HIGH STREET  
NEWARK, NJ 07102  
ATTN DR. R. A. COMPARIN  
ATTN DR. R. Y. CHEN

NASA LANGLEY RESEARCH CENTER  
HAMPTON, VA 23665  
ATTN MS 494, H. D. GARNER  
ATTN MS 494, R. R. HELLBAUM  
ATTN MS 185, TECHNICAL LIBRARY

# DISTRIBUTION (Cont'd)

OHIO STATE UNIVERSITY LIBRARIES  
SERIAL DIVISION, MAIN LIBRARY  
1858 NEIL AVENUE  
COLUMBUS, OH 43210

OKLAHOMA STATE UNIVERSITY  
SCHOOL OF MECH & AEROSPACE ENGR.  
STILLWATER, OK 74074  
ATTN PROF. KARL N. REID

PENNSYLVANIA STATE UNIVERSITY  
215 MECHANICAL ENGINEERING BUILDING  
UNIVERSITY PARK, PA 16802  
ATTN DR. J. L. SHEARER

FRANKLIN INSTITUTE OF THE STATE OF PENNSYLVANIA  
20TH STREET & PARKWAY  
PHILADELPHIA, PA 19103  
ATTN KA-CHEUNG TSUI, ELEC ENGR DIV  
ATTN C. A. BELSTERLING

PENNSYLVANIA STATE UNIVERSITY  
ENGINEERING LIBRARY  
201 HAMMOND BLDG  
UNIVERSITY PARK, PA 16802  
ATTN M. BENNETT, ENGINEERING LIBRARIAN

PURDUE UNIVERSITY  
SCHOOL OF MECHANICAL ENGINEERING  
LAFAYETTE, IN 47907  
ATTN PROF. VICTOR W. GOLDSCHMIDT  
ATTN PROF. ALAN T. MCDONALD

ROCK VALLEY COLLEGE  
3301 NORTH MULFORD ROAD  
ROCKFORD, IL 61101  
ATTN KEN BARTON

RUTGERS UNIVERSITY  
LIBRARY OF SCIENCE & MEDICINE  
NEW BRUNSWICK, NJ 08903  
ATTN GOVERNMENT DOCUMENTS DEPARTMENT,  
MS. SANDRA R. LIVINGSTON

SYRACUSE UNIVERSITY  
DEPARTMENT OF MECHANICAL & AEROSPACE ENGINEERING  
139 E. A. LINK HALL  
SYRACUSE, NY 13210  
ATTN PROF. D. S. DOSANJH

UNIVERSITY OF TEXAS AT AUSTIN  
DEPARTMENT OF MECHANICAL ENGINEERING  
AUSTIN, TX 78712  
ATTN DR. A. J. HEALEY

TULANE UNIVERSITY  
DEPARTMENT OF MECHANICAL ENGINEERING  
NEW ORLEANS, LA 70118  
ATTN H. F. HRUBECKY

UNION COLLEGE  
MECHANICAL ENGINEERING  
SCHENECTADY, NY 12308  
ATTN ASSOCIATE PROFESSOR W. C. AUBREY, MECHANICAL  
ENGINEERING DEPARTMENT, STEINMETZ HALL

VIRGINIA POLYTECHNIC INSTITUTE & STATE UNIVERSITY  
MECHANICAL ENGINEERING DEPARTMENT  
BLACKSBURG, VA 24061  
ATTN PROF. H. MOSES

WASHINGTON UNIVERSITY  
SCHOOL OF ENGINEERING  
P. O. BOX 1185  
ST. LOUIS, MO 63130  
ATTN W. M. SWANSON

WEST VIRGINIA UNIVERSITY  
MECHANICAL ENGINEERING DEPARTMENT  
MORGANTOWN, WV 26505  
ATTN DR. RICHARD A. BAJURA

WICHITA STATE UNIVERSITY  
WICHITA, KS 67208  
ATTN DEPT AERO ENGR, E. J. RODGERS

UNIVERSITY OF WISCONSIN  
MECHANICAL ENGINEERING DEPARTMENT  
1513 UNIVERSITY AVENUE  
MADISON, WI 53706  
ATTN FEDERAL REPORTS CENTER  
ATTN NORMAN H. BEACHLEY, DIR, DESIGN ENGINEERING LAB

WORCESTER POLYTECHNIC INSTITUTE  
WORCESTER, MA 01609  
ATTN GEORGE C. GORDON LIBRARY (TR)  
ATTN TECHNICAL REPORTS

US ARMY ELECTRONICS RESEARCH & DEVELOPMENT COMMAND  
ATTN WISEMAN, ROBERT S., DR., DRDEL-CT  
ATTN PAO  
ATTN MANION, F., DRDEL-AP-CCM

HARRY DIAMOND LABORATORIES  
ATTN 00100, COMMANDER/TECHNICAL DIR/TSO  
ATTN CHIEF, 00210  
ATTN CHIEF, DIV 10000  
ATTN CHIEF, DIV 20000  
ATTN CHIEF, DIV 30000  
ATTN CHIEF, DIV 40000  
ATTN CHIEF, LAB 11000  
ATTN CHIEF, LAB 13000  
ATTN CHIEF, LAB 15000  
ATTN CHIEF, LAB 21000  
ATTN CHIEF, LAB 22000  
ATTN CHIEF, LAB 34000  
ATTN CHIEF, LAB 36000  
ATTN CHIEF, LAB 47000  
ATTN CHIEF, LAB 48000  
ATTN RECORD COPY, 94100  
ATTN HDL LIBRARY, 41000 (5 COPIES)  
ATTN HDL LIBRARY (WOODBIDGE)  
ATTN CHAIRMAN, EDITORIAL COMMITTEE  
ATTN TECHNICAL REPORTS BRANCH, 41300  
ATTN LEGAL OFFICE, 97000  
ATTN LANHAM, C., 00210  
ATTN WILLIS, B., 47400  
ATTN CHIEF, BRANCH 13300  
ATTN CHIEF, BRANCH 13400 (10 COPIES)  
ATTN DRZEWIECKI, T., 13400 (10 COPIES)